

POWERGRIP

Condizionatori di rete

Listino prezzi **marzo 2023**



YG-3

Euro 2.670,00

ELECTRICAL CHARACTERISTICS

Voltage range for safe continuous operation of YG-3 PSU	160 – 320 V
Maximum current of the internal wiring of the console	25 A
Maximum current of power cord and power socket	16 A
Self power consumption	1.4 W – 20 W depends on used features
Consumption in case of full power off by button 2	0 W
Neutral pass through resistance	< 0.00005 Ohm
Live pass through resistance (high current hi-fi filter without fuse and fuse holder)	0.015 Ohm
Fuse	Resistance 0.01 Ohm (with holder), size 5 x 20mm, current 16 A
DC measure range	± 999 mV
Maximum filtering DC value	1.8 V
Maximum on/off delay	60 sec

PROTECTION PARAMETERS

Protection voltage range (turn off connected devices) low: 190 V, high: 256 V

May be influenced by other parameters like mains distortion to provide best protection and exclude false triggering

High Voltage Surge Protection Varistors

SETUP AND CONTROL

Controls	7 sensor buttons and full of switch on a bottom
Remote control	Wi-Fi (Ewelink APP)
Integration (RTI, Control4, Crestron etc.)	Trigger, RS232, Ethernet (option)
Screen menu	Brightness, color, style, filtration, always on sockets, delays
Auto switch on	Power sensor (detect connected device power state), light sensor

PACKAGE INCLUDES

Power console
Power cord (2 m)
Rack mounts
Antenna grounding cable
Direct power cord connection blanket

PACKAGE

GENERAL DATA

Number of sockets	12
Power cable cross size	3.3 mm ²
Cross size of power cables internal wiring	3.3 mm ² (High current Hi-Fi section)
Console weight	7.6 kg
Dimensions (H x W x D)	156.5 x 440 x 280 mm (incl feet)

POWERGRIP

Condizionatori di rete

Listino prezzi **marzo 2023**



YG-2

Euro 1.075,00

ELECTRICAL CHARACTERISTICS

Voltage	190 - 256V
Capacity (at 230V)	3.680W
Rated current	16A

PROTECTED LINES

220V AC Sockets	6
AC line types	Analog, Digital, High Current
COAX lines	1

PROTECTION PARAMETERS

Emergency limits	$\leq 190 \pm 4V / \geq 256 \pm 4V$
Peak current	65.000A

SETUP AND CONTROL

Manual control	Multifunctional button on face-plate and touch sensor
ON/OFF scenarios	Adjustment of delays between socket groups
12V trigger	IN / OUT
RS232 integration	Control4, Crestron, AMX etc.

PACKAGE INCLUDES

AC power cord	1.5 m (optionally - 3 m)
19" rack mounts	Included

GENERAL DATA

Faceplate material	Brushed 4mm aluminum
Overall dimensions (WxHxD)	440 x 80 x 185 mm
Weight	4.8 kg