

# POWERGRIP

Condizionatori di rete

Listino prezzi **luglio 2023** IVA inclusa



## YG-3

**Euro 2.670,00**

### ELECTRICAL CHARACTERISTICS

<b>Voltage range for safe continuous operation of YG-3 PSU</b>	160 – 320 V
<b>Maximum current of the internal wiring of the console</b>	25 A
<b>Maximum current of power cord and power socket</b>	16 A
<b>Self power consumption</b>	1.4 W – 20 W depends on used features
<b>Consumption in case of full power off by button 2</b>	0 W
<b>Neutral pass through resistance</b>	< 0.00005 Ohm
<b>Live pass through resistance (high current hi-fi filter without fuse and fuse holder)</b>	0.015 Ohm
<b>Fuse</b>	Resistance 0.01 Ohm (with holder), size 5 x 20mm, current 16 A
<b>DC measure range</b>	± 999 mV
<b>Maximum filtering DC value</b>	1.8 V
<b>Maximum on/off delay</b>	60 sec

### PROTECTION PARAMETERS

<b>Protection voltage range (turn off connected devices)</b>	low: 190 V, high: 256 V
--	-------------------------

May be influenced by other parameters like mains distortion to provide best protection and exclude false triggering

<b>High Voltage Surge Protection</b>	Varistors
--------------------------------------	-----------

### SETUP AND CONTROL

<b>Controls</b>	7 sensor buttons and full of switch on a bottom
<b>Remote control</b>	Wi-Fi (Ewelink APP)
<b>Integration (RTI, Control4, Crestron etc.)</b>	Trigger, RS232, Ethernet (option)
<b>Screen menu</b>	Brightness, color, style, filtration, always on sockets, delays
<b>Auto switch on</b>	Power sensor (detect connected device power state), light sensor

### PACKAGE INCLUDES

Power console  
Power cord (2 m)  
Rack mounts  
Antenna grounding cable  
Direct power cord connection blanket

### PACKAGE

### GENERAL DATA

<b>Number of sockets</b>	12
<b>Power cable cross size</b>	3.3 mm <sup>2</sup>
<b>Cross size of power cables internal wiring</b>	3.3 mm <sup>2</sup> (High current Hi-Fi section)
<b>Console weight</b>	7.6 kg
<b>Dimensions (H x W x D)</b>	156.5 x 440 x 280 mm (incl feet)

# POWERGRIP

Condizionatori di rete

Listino prezzi **luglio 2023** IVA inclusa



## YG-2

Euro 1.075,00

### ELECTRICAL CHARACTERISTICS

<b>Voltage</b>	190 - 256V
<b>Capacity (at 230V)</b>	3.680W
<b>Rated current</b>	16A

### PROTECTED LINES

<b>220V AC Sockets</b>	6
<b>AC line types</b>	Analog, Digital, High Current
<b>COAX lines</b>	1

### PROTECTION PARAMETERS

<b>Emergency limits</b>	$\leq 190 \pm 4V / \geq 256 \pm 4V$
<b>Peak current</b>	65.000A

### SETUP AND CONTROL

<b>Manual control</b>	Multifunctional button on face-plate and touch sensor
<b>ON/OFF scenarios</b>	Adjustment of delays between socket groups
<b>12V trigger</b>	IN / OUT
<b>RS232 integration</b>	Control4, Crestron, AMX etc.

### PACKAGE INCLUDES

<b>AC power cord</b>	1.5 m (optionally - 3 m)
<b>19" rack mounts</b>	Included

### GENERAL DATA

<b>Faceplate material</b>	Brushed 4mm aluminum
<b>Overall dimensions (WxHxD)</b>	440 x 80 x 185 mm
<b>Weight</b>	4.8 kg